

ML3410 DOT MATRIX PRINTER



❖❖❖ ML3410

❖❖❖ 9-PIN DOT MATRIX PRINTER

POWER, RELIABILITY AND VERSATILITY FROM A SINGLE PRINTER

The ML3410 is a powerful dot matrix printer designed to handle the most data-intensive applications at very high speeds. Its copy capabilities are impressive producing up to eight multi-part copies at any one time.

MAIN FEATURES OF THE ML3410 PRINTER

- ❖❖❖ 136 column dot matrix printer
- ❖❖❖ Extremely durable 9-pin print head with Oki reliability built-in
- ❖❖❖ Up to 550 characters per second print speed
- ❖❖❖ Multi-part paper-handling (original + 7 copies)
- ❖❖❖ Ideal for purchasing and distribution, and Accounts, Finance and IT departments that require high speed, high volume printouts



OKI

ML3410 DOT MATRIX PRINTER

PRODUCT SPECIFICATION

		ML3410
General	Number of pins	9
	No. of multi-part forms	8 (one original + 7 copies)
Speed & throughput	High speed draft (12cpi & 10cpi)	550cps
	Utility (12cpi & 10cpi)	417cps
	Near letter quality (12cpi & 10cpi)	104cps
	Fastest print speed (10cpi)	550cps
Font & print features	Carriage width (10cpi)	136 columns
	Max. in compressed mode	272 columns
	Character pitch	10/12/15/17.1/20 pitch & proportional
	Graphics resolution	Up to 240 x 216 dpi
	Typeface & Font	NLQ-Courier, NLQ-Gothic, OCR-B, High Speed Draft, Utility + Barcodes
	Typestyle	Emphasised, Enhanced, Double Width, Double Height, Italics, Bold, Superscript, Subscript, Underline, Overscore
Emulations & interfaces	Printer emulations	Epson FX, IBM ProPrinter XL or Oki MICROLINE/PM (optional)
	Standard interfaces	Centronics Parallel, Serial RS 232C, dual interface
Paper-handling	Continuous paper	76—406mm
	Continuous envelopes	239 x 102mm
	First printable line (from top of page)	Cut sheet: 25.4mm Continuous: 23.3mm
	Standard	Autoload single sheet, Paper parking, Rear push tractors, Metal long-life tear-off bar
	Optional	Single/dual bin sheet feeder, Pull tractor, Bottom power push tractor
Physical	Dimensions (HxWxD)	180 x 570 x 417mm
	Weight	18kg
	Memory (Total RAM)	Standard buffer 28KB (reduced buffer)
	Noise level (ISO 7779)	<58dB(A)
Power	Power requirements	230V AC
	Frequency	50/60Hz
Reliability	Print head life	200 million characters
	Ribbon life	10 million characters
Supplies life	MTBF	8,000 hours

OKI

*Oki, Network Solutions
for a Global Society*

OKI SYSTEMS (UK) LTD, PART OF OKI ELECTRIC

OKI SYSTEMS (UK) LTD,
550 DUNDEE ROAD,
SLOUGH, BERKSHIRE
SL1 4LE
UNITED KINGDOM

TEL: +44 (0)1753 819819
FAX: +44 (0)1753 819899

WWW.OKI.CO.UK



As an ENERGY STAR Partner, Oki Europe Ltd
has determined that this product meets the
ENERGY STAR guidelines for energy efficiency

09400922
© 2003 Oki Europe Ltd.